Van Stone Mine

Assessment and Overview of Reclamation Alternatives



Presented by John Haney, PE and Dustin Wasley, PE May 3, 2016



0





Site History

- Discovered by George Van Stone in 1920 while hunting
- 3,638 feet in the Kootenay Arc Structural Belt
- Part of the Northport (Aladdin) Mining District
- Zinc/lead ore produced between 1920 and 1993
- Carbonate host rock (Dolomite)



Mine Ownership

- George Van Stone 1920 to 1926
- Hecla 1926 to 1930
- Willow Creek Mines 1939 to 1950
- ASARCO 1950 to 1971
- Callahan Mining Corp./US Borax and Chemical Corporation/Newfoundland Exploration Ltd. – 1971 to 1990
- Equinox Resources 1990 to 2009
- African Aura Mining 2009 to?



Production

Underground working until ASARCO

- ASARCO constructed a 1,000-ton/day
 Floatation Mill
- Zinc cons shipped to Anaconda Copper Company's smelter
- Lead cons shipped to ASARCO's East Helena smelter

GEOENGINEERS /



Production

- 1961 Upper Tailings Pond failed into Onion Creek
- 1965 to 1966 (top years) avg. 820 tons zinc/month
- By 1976 total output for the mine was 25M lbs. lead and 188M lbs. zinc
- ASARCO mined 7.5M tons (2.7M tons of ore) from the North and South Pits
- Mill was dismantled in 2006 and shipped to Canada













North Pit





North Pit





South Pit



Overburden/Waste Rock Near South Pit









Washington Department of Ecology Involvement

- Site Hazard Assessment conducted 2007
- Site ranked 1 out of 5 (1 = highest risk)
- Equinox entered Ecology's Voluntary Cleanup Program
- Due to lack of adequate progress, Ecology moved the Site into formal cleanup under authority of the Model Toxics Control Act (MTCA)
- In 2010 Ecology received a settlement from a lawsuit against ASARCO (\$3.5M)









June 26, 2012



June 26, 2012



June 26, 2012



October 10, 2012





October 10, 2012



October 10, 2012







Lower Tailings Pile



Upper Tailings Pile





Mill Area



Human & Ecological Risk Drivers

- Chemical
 - Antimony (2.6 ppm)
 - Arsenic (30.8 ppm)
 - Cadmium (105 ppm)
 - Lead (14,700 ppm)
 - Zinc (57,200 ppm)
- Physical
 - High wall hazard
 - Landslide potential into pit lake
 - Slope failure of tailings



Reclamation Alternatives

- No Action
- Institutional Controls
- Cap in-place
- Consolidation
 - Consolidate Upper with Lower and cap in-place
 - Consolidate Upper and Lower in centralized repository
 - Consolidate in the open pit
- Offsite Disposal

